



Double walled Pickup tank ALU

When lightness matters!



Lightweight and safe fuel tank



Our double walled pickup tank is a extremely lightweight and convenient ADR fuel tank that has an aluminum inner and outer tank. It works as an environmentally safe and secure tank for fuel distribution even with small pickups or as a rigid easy to handle tank on the ground

The aluminium pickup tank is suitable for:

- Civil engineering
- Forestry
- Haulage

Certifications & approvals

The product is approved and certified as IBC container (Intermediate Bulk Container) in accordance with the following regulations and recommendations:

UN (UN's recommendations for transport of diesel etc.)

ADR (European regulations for international road transport of diesel etc.)

RID (international regulations for rail transport of diesel etc.)

IMDG (code for international maritime transport of diesel etc.)

PEFC (PEFC is a system for sustainable forestry certification)



About MPP

MPP is a family-owned company in Fjärps, western Sweden, which has been operating on the Scandinavian market since 2004.

We design and sell sustainable fuel tanks, diesel cisterns and fuel facilities for secure storage, handling and transport of fuels. Our target group are primarily rental, construction, haulage, forestry and agricultural companies, which, just like us, have high ambitions concerning quality, safety and the environment.

Our brand promise is: **Safe and flexible fuel handling**

Standard equipment



Easy accesable pump thanks to our cab lid. The tank is designed to fit between the wheel arches of most trucks.



Removable aluminum inner-tank for easy inspection and maintenance. Low weigh tank to reduce vehicle wear.



Lifting handle designed to secure with lifting straps.



2 "analog level gauge, 2" tank cap, 1 "pressure / vacuum release valve.



Spill Containment

The fuels are filled in the pump cabinet, which is equipped with a spill containment that prevents pumps, connections, and other accessories from causing spill. In the event of overfilling, the fuel flows to the spill containment.



Hose lead-through (plugged) for continual feed, whilst lid remains locked.



2 lifting handles on both sides.



Lockable cabinet fitted with a safety lead.



1 extra 3/4" suction pipe for quick coupling.



Double Walled

Environmental approved, double walled tank with a 110% spill containment to comply with the requirements of NFS 2017: 5 regulation and MSBFS 2018: 3 regulations.



Tank specifications

Product no.:	101515	101517
Description:	DM Pickuptank ALU 150 l	DM Pickuptank ALU 250 l
Designation:	PTA 15-DM	PTA 25-DM
Volume, 95% (l)*:	150 L	250 L
Length (mm)**:	1120	1120
Width (mm)**:	430	600
Height (mm)**:	785	785
Net (kg)***:	109	138
Gross (kg) ****:	240	363

*Estimated volume **Stated dimensions +-10 mm.

***Estimated weight when fully equipped with pump gear installed.

****+-100kg.

Accessories

- Pump kit 12 V12 V, 36 l/min*
- Pump kit 24/12 V, 39/22 l/min*
- Runners (for lifting by forklift), 400 l

Art.nr:

100231
101016
100134

* Package including automatic refuelling nozzle, 4-metre refuelling hose, 4-metre cable with battery connectors, 1 right-mounted diesel handle holder, 1 refuelling hose holder and bolts and lock nuts.

Last updated: 24 January 2022